




# MSL Procedure Light



**Light source** - 3 x compact LED modules comprising 7 LEDs, driver and lens specifically designed for medical lighting tasks.

**Wattage** - 3 x 10W.

**Dimming** - 4 stage electronic dimming.

**Illumination** – 74,200 lux @ 1000mm - 83,300 lux @ 600mm

**Light source average life** - 35,000-50,000 hours

**Beam diameter** - 126mm\* @ 1000mm - 144mm\* @ 600mm  
(\* measured at 50% of peak value).

**Colour temperature** - 4089°K.

**Colour Rendering Index** - CRI 96. In addition, the LED module has a high 'Special CRI R9' value (deep saturated red, not included in normal CRI calculations). For medical examination lighting tasks this R9 value is a key issue in diagnosis and accurate tissue identification.

The MSL - SL319C complies with the **Cyanosis Observation Index (COI)**, meeting the requirements of AS/NZS 1680.2.5:1997 for examination lighting

**Cardiac protection** - compliant.

**Voltage** - 36V DC.

**EMC** – compliant.


**Weight** - 17kg

## MSL319C NEW Features:

MSL's patent pending support arm provides effortless movement requiring no on-going adjustment and is maintenance free.

360-degree rotation at both the upper and lower arms is now standard.

Extended upper & lower arms for greater patient coverage.



**Dimensions & range of movement**



Check out our website at [www.vet1.com.au](http://www.vet1.com.au) or e-mail [sales@vet1.com.au](mailto:sales@vet1.com.au) or call us on **1300 378 713** to discuss anything Veterinary Equipment related. We are Committed to Quality.